

Low Loader Trombone

This Low loader packs many features which makes it a very versatile unit.

It can be used as a standard Low loader trailer with its ramps, or the ramps can be removed to allow a load overhang out over the rear.

The unit can be extended out from the bottom of the step deck to increase the deck length.

There are also riser attachments that can allow for the bottom deck to be at the same height as the top deck



Payload	16,000kg	Lower Deck Height	0.9m
Deck size	Refer to chart below	Upper Deck Height	1.5m
Deck width	2.5m	Tare weight	5,750kg

Trombone Lengths

Trombone Lowloader

	Closed	1st Lock	2nd Lock	3rd Lock	4th Lock	5th Lock	6th Lock	7th Lock	8th Lock	9th Lock
Forward Distance	8.54	9.19	10.45	11.69	12.0	12.43	13.0	13.54	14.0	14.63
Bottom Deck length	9.3	9.7	11.2	12.42	12.8	13.2	13.8	14.3	14.8	15.4
Total Deck Length	12.3	12.7	14.2	15.42	15.8	16.2	16.8	17.3	17.8	18.4

Note: trailer extends from bottom of step deck

Low Loader Pilot and Permit Requirements

Any position if rear overhang is 7mtrs or more	1x Pilot
3 rd Lock to 6 th lock	1x Pilot
3 rd Lock and rear overhang is more than 7mtrs	2x Pilots
7 th to 9 th Lock	Permit and 2x pilots
7 th to 9 th Lock and rear overhang is more than 7mtrs	Permit and 3x pilots

Note: Rear overhang is measured from the centre of the middle axle to the rear most part of the load.

Forward distance is measured from the centre of the middle axle to the king pin.

Front overhang .8mtr/Rear ramps 1.2mtr

All information given are for reference only