

Trombone Trailer

Configured with a standard trombone extension in the middle of the deck and a wind out support extending from the rear of the trailer. With both parts stretched to their max this trailers length is 24.3m



| | | | |
|------------|----------------------|-------------|---------|
| Payload | | Deck Height | 1.3m |
| Deck size | Refer to chart below | Tare weight | 8,300kg |
| Deck width | 2.5m | | |

Trombone Lengths

Trombone Trailer

| | REAR O/H | Closed | 1st Lock | 2nd Lock | 3rd Lock | 4th lock | 5th lock | 6th lock |
|-----------------|----------|--------|----------|----------|----------|----------|----------|----------|
| FWD | - | 3.5 | 4 | 4.5 | 5 | 5.5 | 6 | 6.5 |
| Closed | 9.2 | 14.4 | 14.9 | 15.4 | 15.9 | 16.4 | 16.9 | 17.4 |
| 1st Lock | 10.3 | 15.5 | 16 | 16.5 | 17 | 17.5 | 18 | 18.5 |
| 2nd Lock | 11.4 | 16.6 | 17.1 | 17.6 | 18.1 | 18.6 | 19.1 | 19.6 |
| 3rd Lock | 13.3 | 18.5 | 19 | 19.5 | 20 | 20.5 | 21 | 21.5 |
| 4th Lock | 14.7 | 19.9 | 20.4 | 20.9 | 21.4 | 21.9 | 22.4 | 22.9 |
| 5th Lock | 16.1 | 21.3 | 21.8 | 22.3 | 22.8 | 23.3 | 23.8 | 24.3 |

Note: Rear wind out not suitable for supporting heavy loads i.e. Structural steel

Pilot and Permit Requirements

| | |
|--|----------------------|
| Any position if rear overhang is 7mtrs or more | 1x Pilot |
| 3 rd FWD Lock | 1x Pilot |
| 3 rd FWD Lock and rear overhang is more than 7mtrs | 2x Pilots |
| 4 th to 6 th FWD Lock | Permit and 2x pilots |
| 4 th to 6 th FWD Lock and rear overhang is more than 7mtrs | Permit and 3x pilots |

Note: Rear overhang is measured from the centre of the middle axle to the rear most part of the load.
Forward distance is measured from the centre of the middle axle to the king pin.

All information given are for reference only